

View Online at <https://aerobasegroup.com/nsn/6220-01-116-2409>

End Application:

F-16 aircraft

Indicator Type:

Light

Panel Material:

Plastic

Special Features:

4 holes 0.220 min, 0.225 maximum in. Radius; 5 grommet holes 0.311 min, 0.318 maximum in.; 1 hole 0.640 min, 0.671 maximum in counterbore fs 1.000, 1.030 in diameter by 0.140 min, 0.160 in. Deep; 1 hole 0.796 min, 0.828 maximum in.; 1 hole 0.906 min, 0.937 maximum in. Counterbore fs 0.735 min, 0.765 maximum diameter by 0.062 min, 0.093 max; 1 hole 0.546 min, 0.578 maximum counterbore fs 0.735 min, 0.765 maximum diameter by 0.125 min 0.156 maximum deep; 3 holes 0.515 min, 0.546 maximum counterbore fs 0.735 min, 0.765 maximum in. Dia, 0.125 min, 0.156 maximum deep; 3 holes 0.515 min, 0.546 maximum in. Counterbore fs 0.735 min, 0.765 maximum diameter by 0.125 min, 0.156 maximum dia; 1 hole 0.625 min, 0.640 maximum in., counterbore fs 0.797 min, 0.812 maximum in. Diameter by 0.125 min, 0.156 maximum in. Deep

Fsc Application Data:

Panel, indicating, light transmitting, landing gear

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T122-b