Electric Floodlight - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6220-01-189-4911

| Rı | ustproof |
|----|-------------------------------------|
| 0 | verall Length: |
| 4. | 000 inches |
| 0 | verall Diameter: |
| 5. | 000 inches |
| La | amp Base Type Accommodated: |
| T٧ | wo screw terminals |
| w | /iring Provision Method: |
| Са | able assembly |
| Li | ight Beam Motion: |
| Fi | xed |
| w | liring Provision Length: |
| Ar | ny acceptable all provisions |
| Vo | oltage Rating In Volts: |
| 12 | 2.0 dc |
| M | ounting Method: |
| Tł | nreaded stud |
| La | amp Type Accommodated And Quantity: |
| 1 | incandescent |
| M | aterial: |
| Rı | ubber natural body |
| Sı | urface Treatment: |
| Ar | ny acceptable body |
| Sł | hape: |
| Та | apered |
| Fι | urnished Items And Quantity: |
| 1 | lamp |
| Te | erminal Type And Quantity: |
| 2 | tab, solder lug |
| Sł | helf Life: |
| N/ | /a |
| Uı | nit Of Measure: |
| | |
| De | emilitarization: |
| No | 0 |
| Fi | ig: |
| A | 06300 |