NSN 6220-01-246-5314

Electric Floodlight - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6220-01-246-5314

| view Online at https://aerobasegroup.com/nsn/6220-01-246-5314 |
|--|
| Hazardous Locations/environmental Protection: |
| Shock and vibration resistant |
| Overall Length: |
| 7.000 inches |
| Overall Diameter: |
| 8.875 inches |
| Lamp Base Type Accommodated: |
| Medium side prong |
| Wiring Provision Method: |
| Cable |
| Light Beam Motion: |
| Fixed |
| Light Adjustment Method: |
| Swivel arm and swivel joint |
| Light Adjustment Limits: |
| 360.0 degrees horizontal |
| Reflector Shape: |
| Parabolic |
| Reflector Inclosure Type: |
| Inclosed singular |
| Wiring Provision Length: |
| 42.0 inches all provisions |
| Voltage Rating In Volts: |
| Between 115.0 ac and 150.0 ac |
| Mounting Method: |
| Bolt |
| Features Provided: |
| Detachable and light adjustment locking device |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Special Features: |
| Super rough service; will accept 12 and 32 volts parabolic 38 lamps |
| Material: |
| Steel illumination directing device |
| Surface Treatment: |
| Enamel baked illumination directing device |
| Shape: |
| Round |
| Terminal Type And Quantity: |
| 1 connector, plug, external, 3 contacts, 1 contact u-shaped for ground |

Shelf Life: N/a

NSN 6220-01-246-5314

Electric Floodlight - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A06300