NSN 6220-01-283-1242

Electric Floodlight - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6220-01-283-1242

| Watertight Overall Length: 2.500 inches Overall Diameter: 4.625 inches Lamp Base Type Accommodated: Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: 1 incandescent |
|---|
| 2.500 inches Overall Diameter: 4.625 inches Lamp Base Type Accommodated: Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Overall Diameter: 4.625 inches Lamp Base Type Accommodated: Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| 4.625 inches Lamp Base Type Accommodated: Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Lamp Base Type Accommodated: Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Two contact lugs Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Wiring Provision Method: Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Individual wire Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Light Beam Motion: Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Fixed Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Reflector Shape: Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Parabolic Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Reflector Inclosure Type: Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Inclosed singular Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Voltage Rating In Volts: 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| 12.0 dc Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Mounting Method: Bracket Lamp Type Accommodated And Quantity: |
| Bracket Lamp Type Accommodated And Quantity: |
| Lamp Type Accommodated And Quantity: |
| |
| 1 incandescent |
| |
| Special Features: |
| Display packed |
| Material: |
| Copper alloy body |
| Surface Treatment: |
| Chromium body |
| Shape: |
| Tapered |
| Furnished Items And Quantity: |
| 1 lamp |
| Terminal Type And Quantity: |
| 1 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A06300