NSN 6220-01-284-1888

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6220-01-284-1888

Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
2.830 inches
Overall Diameter:
1.120 inches
Lamp Base Type Accommodated:
Double contact bayonet candelabra
Lamp Bulb Size Designator:
S-6
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
1.000 inches
End Application:
Crane, a/c crash & salvage, a/s32p
Lens Mounting Method:
Screw on
Mounting Method:
Mounting Method: Panel
-
Panel
Panel Thickness For Which Designed:
Panel Panel Thickness For Which Designed: 0.062 inches
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity:
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type:
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition:
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Frosted single light 1st position horizontal
Panel Thickness For Which Designed: 0.062 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Frosted single light 1st position horizontal Material:

Furnished Items And Quantity: 1 hexagon nut and 1 lock washer

NSN 6220-01-284-1888

Indicator Light - Page 2 of 2



Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0