## NSN 6220-01-390-0783

Light Transmitting Indicating Panel - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6220-01-390-0783

| Overall Length:   |
|---|
| 5.570 inches  |
| Overall Height:   |
| 10.720 inches   |
| Ac Voltage Rating:  |
| 115.0 volts   |
| Overall Thickness:  |
| Between 0.230 inches and 0.243 inches   |
| End Application:  |
| Helicopter, uh-60a/uh-60d   |
| Indicator Type:   |
| Light   |
| Panel Material:   |
| Plastic, mil-p-5425   |
| Special Markings:   |
| Formaton It; 1; 2; 3; 4; 5; off; glareshield lights; off; brt; lighted switches; off; brt; lighted inst Its; off; brt; nav Its; norm; ir; cargo tail; |
| hook lt; posn lt; off; tail posn lt; cabin dome lt; white; off; blue; anti collision lights; norm; day; ir; stdy; upper; both; lower; off; night      |
| flash; 1; 2; 3; 4; 5; ir brt; position lights; dim; steady; off; brt; flash; backup hyd pump; off; auto; on; hyd leak test; reset; norm;              |
| test  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| T122-b  |
|   |
|   |