

View Online at <https://aerobasegroup.com/nsn/6220-01-406-8960>

**Hazardous Locations/environmental Protection:**

Cold resistant and dripproof and electromagnetic radiation suppressive and fungus resistant and heat resistant and moisture resistant and radio frequency interference and salt spray resistant and shock resistant and splashproof and watertight

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Lamp Base Type Accommodated:**

Submidget flanged

**Lamp Bulb Size Designator:**

T-1

**Lens Quantity:**

1

**Lens Color:**

Black, opaque single light 1st position horizontal

**Multilamp Circuit Type:**

Four lamp separate

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

Between 0.032 inches and 0.187 inches

**Panel Accommodation Hole Width:**

Between 0.696 inches and 0.706 inches

**Lamp Type Accommodated And Quantity:**

4 incandescent

**Lens Type:**

Flat, rectangular, framed single light 1st position horizontal

**Panel Accommodation Hole Height:**

Between 0.696 inches and 0.706 inches

**Lens Light Transmission Characteristic:**

Translucent single light 1st position horizontal

**Transmitted Legend Color:**

Red single light 1st position horizontal horizontal split display division b

**Lens Legend:**

Go single light 1st position horizontal horizontal split display division a

**Transmitted Light Color:**

Black, opaque single light 1st position horizontal horizontal split display division b

**Lens Back Surface Condition:**

Smooth single light 1st position horizontal

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Special Features:**

Explosion per mil-s-22885 and mil-std-202, method 109; common terminaton system (cts) connector

**Material:**

Stainless steel body

**Style Designator:**

Rectangular frame type

**Furnished Items And Quantity:**

1 mounting sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A065a0