

View Online at <https://aerobasegroup.com/nsn/6220-01-406-8960>

Hazardous Locations/environmental Protection:

Cold resistant and dripproof and electromagnetic radiation suppressive and fungus resistant and heat resistant and moisture resistant and radio frequency interference and salt spray resistant and shock resistant and splashproof and watertight

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Lamp Base Type Accommodated:

Submidget flanged

Lamp Bulb Size Designator:

T-1

Lens Quantity:

1

Lens Color:

Black, opaque single light 1st position horizontal

Multilamp Circuit Type:

Four lamp separate

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.032 inches and 0.187 inches

Panel Accommodation Hole Width:

Between 0.696 inches and 0.706 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, rectangular, framed single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.696 inches and 0.706 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

Red single light 1st position horizontal horizontal split display division b

Lens Legend:

Go single light 1st position horizontal horizontal split display division a

Transmitted Light Color:

Black, opaque single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Special Features:

Explosion per mil-s-22885 and mil-std-202, method 109; common terminaton system (cts) connector

Material:

Stainless steel body

Style Designator:

Rectangular frame type

Furnished Items And Quantity:

1 mounting sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0