

View Online at <https://aerobasegroup.com/nsn/6230-00-264-8261>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

8.500 inches

**Overall Diameter:**

2.250 inches

**Lamp Base Type Accommodated:**

Single contact miniature flanged

**Lens Color:**

Colorless

**Lens Transparency:**

Transparent

**Light Beam Motion:**

Fixed and flashing

**End Application:**

Torpedo, adcap 48; m1a2 heavy assault bridge (hab) wolverine, 5420-01-430-4247; spruance class d (963); armored vehicle launch bridge (m60a1 & m48a5); m1a2 system enhancement prog 2350-01-328-5964 (eaa cmbt85sep); ticonderoga class cg(47); field artillery ammunition support vehicle(faagv)(m992); deep submergence systems programs (dssp); m1a2 abrams tank, 2350-01-328-5964 (eaa cmbt85pk3) ; pads, an/usq-70; floating causeway; roll on/roll off discharge facility

**Voltage Rating In Volts:**

3.0 dc

**Mounting Method:**

Ring

**Features Provided:**

Switch and replaceable battery and removable light filter

**Lamp Type Accommodated And Quantity:**

1 incandescent

**Lens Type And Quantity:**

1 flat, round

**Battery Type And Quantity Required:**

2 dry

**Lens Surface Condition:**

Smooth back

**Special Features:**

Compartment, storage contains 1 diffused lens, 1 blackout filter, 2 red filters and 1 blue filter

**Material:**

Plastic polycarbonate lens

**Material Specification:**

L-p-393 federal specification single material response lens

**Surface Treatment:**

Vacuum plated or electro plated reflector

**Shape:**

Right angle

**Furnished Items And Quantity:**

2 lamp

**Terminal Type And Quantity:**

1 spring, compression

**Specification Or Standard:**

1 type and 2 style and 2 cell cz

**Departure From Cited Designator:**

As modified by olive drab color

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A06300

**Mil-std (military Standard):**

Mil-f-3747 spec.