NSN 6230-00-270-5417

Flashlight - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6230-00-270-5417 |
|--|
| Hazardous Locations/environmental Protection: |
| Explosion proof nec cl.I, gp.Cd; cl.Ii, gp.Efg; cl.Iii and watertight |
| Overall Length: |
| 11.000 inches |
| Overall Diameter: |
| 3.000 inches |
| Lamp Base Type Accommodated: |
| Single contact miniature flanged |
| Lens Color: |
| Colorless |
| Lens Transparency: |
| Transparent |
| Light Beam Motion: |
| Fixed |
| Voltage Rating In Volts: |
| 4.5 dc |
| Mounting Method: |
| Ring |
| Features Provided: |
| Switch |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Lens Type And Quantity: |
| 1 flat, round |
| Battery Type And Quantity Required: |
| 3 dry |
| Lens Surface Condition: |
| Smooth back |
| Material: |
| Plastic polycarbonate lens |
| Material Specification: |
| Mil-m-14, ty cfi-20 military specification single material response body |
| Surface Treatment: |
| Vacuum plated or electro plated reflector |
| Shape: |
| Straight |
| Furnished Items And Quantity: |

2 lamp

Terminal Type And Quantity:

1 spring

Specification Or Standard:

lii type and 1 style and 3 size

NSN 6230-00-270-5417

Flashlight - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A06300 | |

Mil-std (military Standard):

Mil-m-14 spec.

Shelf Life: