

View Online at <https://aerobasegroup.com/nsn/6230-00-299-3035>

Hazardous Locations/environmental Protection:

Explosion proof nec cl.I, gp.Cd; cl.Ii, gp.Efg; cl.Iii and watertight and heat resistant

Overall Length:

8.250 inches

Overall Diameter:

3.000 inches

Lamp Base Type Accommodated:

Single contact miniature flanged

Lens Color:

Colorless

Lens Transparency:

Transparent

Light Beam Motion:

Fixed and flashing

Voltage Rating In Volts:

3.0 dc

Mounting Method:

Ring

Features Provided:

Switch and replaceable battery

Lamp Type Accommodated And Quantity:

1 incandescent

Lens Type And Quantity:

1 plano convex

Battery Type And Quantity Required:

2 dry

Lens Surface Condition:

Smooth back

Environmental Attribute Code:

Plastics removal in the marine environment (prime) product

Special Features:

Explosion-proof and heat-resistant flashlight is specifically designed to resist dust, water and fumes; especially suited for use in areas where danger is present from possible explosion of combustible gases, dusts or explosives; features a three-way switch for on, off and flasher functions; includes one pr-6 bulb installed plus one spare bulb; requires two d cell batteries (not included)

Material:

Plastic body

Material Specification:

Mil-m-14, type cfi-20 military specification single material response body

Shape:

Tapered

Furnished Items And Quantity:

2 lamp and 1 lens

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06300

Mil-std (military Standard):

Mil-m-14 spec.