NSN 6230-00-926-4331

Flashlight - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6230-00-926-4331 |
|---|
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 15.250 inches |
| Overall Diameter: |
| 2.250 inches |
| Lamp Base Type Accommodated: |
| Single contact miniature flanged |
| Lens Color: |
| Colorless |
| Lens Transparency: |
| Transparent |
| Light Beam Motion: |
| Fixed and flashing |
| Voltage Rating In Volts: |
| 3.0 dc |
| Mounting Method: |
| Ring |
| Features Provided: |
| Switch and replaceable battery and removable light filter |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Lens Type And Quantity: |
| 1 convex, straight side, semi-dome |
| Battery Type And Quantity Required: |
| 2 dry |
| Lens Surface Condition: |
| Smooth back |
| Environmental Attribute Code: |
| Plastics removal in the marine environment (prime) product |
| Special Features: |
| Specially designed for directing vehicular traffic and for other signaling purposes; straight plastic body with cone-shaped traffic baton; |
| 30-1/2" long nylon cord affixed to mounting ring; features a three-way switch for on, off and flasher functions; multi-colored (red, amber, |
| green, blue, and blackout) removable filers are provided; comes with one pr-6 bulb installed, plus one spare bulb; requires two d cell |
| batteries (not included); color-gray |
| Material: |
| Plastic body |
| Shape: |
| Straight |
| Furnished Items And Quantity: |
| 2 lamp |
| Terminal Type And Quantity: |

As modified by gray color

Departure From Cited Designator:

2 any acceptable

NSN 6230-00-926-4331

Flashlight - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A06300 | |

Mil-std (military Standard):

Mil-f-3747 spec.

Shelf Life: