NSN 6230-01-247-3609

Hazardous Locations/environmental Protection:

Electric Floodlight - Page 1 of 2

Lamp Base Type Accommodated:

Weatherproof



View Online at https://aerobasegroup.com/nsn/6230-01-247-3609

1 connector, plug, external, 3 contacts, 1 contact u-shaped for ground

Recessed single contact
Lens Color:
Colorless
Lens Transparency:
Transparent
Wiring Provision Method:
Cable assembly
Light Beam Motion:
Fixed
Light Adjustment Method:
Tilting arm
Reflector Shape:
Concave
Reflector Inclosure Type:
Inclosed singular
Wiring Provision Length:
72.0 inches single provision
Voltage Rating In Volts:
120.0 ac
Mounting Method:
Magnetic
Features Provided:
Switch
Lamp Type Accommodated And Quantity:
1 incandescent
1 incandescent Lens Type And Quantity:
Lens Type And Quantity:
Lens Type And Quantity: 1 flat, rectangular
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition:
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features:
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features: Can be plate mtd w/screws
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features: Can be plate mtd w/screws Material:
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features: Can be plate mtd w/screws Material: Glass lens
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features: Can be plate mtd w/screws Material: Glass lens Shape:
Lens Type And Quantity: 1 flat, rectangular Lens Surface Condition: Smooth back Special Features: Can be plate mtd w/screws Material: Glass lens Shape: Rectangular

NSN 6230-01-247-3609

Electric Floodlight - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06300