NSN 6240-00-144-4566

Incandescent Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-00-144-4566

| Overlands 0.187 inches 1.375 inches Filemet Designation: C-27 Average Life Rating In Hours: 100000.0 Filemet Heavy Duty Service Rating: Not rated Marginet Heavy Duty Service Rating: Not rated Average Life Rating In Hours: 10000.0 Filemet Heavy Duty Service Rating: Not rated Average Life Rating In Hours: Average Life Rating In Hours: Average Life Rating In Hours: Average Life Rating: aviarrat, vining s-3b; aircraft, tomeat f-14; aircraft, hawkeye e-2c; ta-4j aircraft; aircraft, c2a (reprocured); helicopter, advance attack; ah-1) Emitted Light Characteristic: Rate Votage Rating: 0.300 volts Watage Rating: 0.300 volts Bub Style: T (tubula) Bub Style: T (tubula) Bub Light Transmission Characteristic: T (tubula) Current Rating For Which Designet: Current Rating For Which Designet: Nava acceptate Aviar acceptate | |
|--|---|
| Note Cale 1.375 indes Filtent Designation: C-2r Areage Life Rating In Hours: 10000.0 Filtent Hoavy Duty Sorice Rating: No rated Ented Light Social Cale Karafi, viking s-3b; aircraft, tomcat f-14; aircraft, hawkeye e-2c; ta-4j aircraft, sicraft, social (reprocured); helicopter, advance attack a'n-4; aircraft, oricn p-3; helicopter, colora/attack, ah-1j Ented Light Characteristic: Rated Valage Rating: 3000 volts Valage Rating: 3000 volts Buts System Valage Rating: 1030 volts Buts System Valage Rating: 1030 volts Buts System Valage Rating: 1030 volts Buts System 104 voltage down 105 voltage Rate System 105 voltage down 105 voltage down 105 voltage down 106 voltage down 107 voltage down 108 voltage down 109 voltage down 1 | Overall Length: |
| 1.375 incles Filament Designation: C-2r Average Life Rating In Hours: 10000.0 Filament Heavy Duty Service Rating: Not raid End Application: Aricraft, wiking s-3b; aircraft, tomat F14; aircraft, hawkeye e-2c; ta-4j aircraft, e-2a (reprocured); helicopter, advance attack ah-1w; aircraft, orion p-3; helicopter, cobra/attack, ah-1j Emitted Light Characteristic: Red Voltage Rating: 5.000 volts Watage Rating: 0.300 volts Base Style: Wite ladd, down Bub Light Transmission Characteristic: T (tubular) Bub Light Transmission Characteristic: Carge Rating: 0.300 volts Bub Light Transmission Characteristic: T (tubular) Bub Light Transmission Characteristic: Carge Rating Powihich Designed: Oxfor Rating Powihich Designed: Carge Rating Powihich Designed: Carge Rating Powihich Designed: Carge Rating Powihich Designed: Carge Rating Powihich Designed: Rate Average Life: Hours | 0.187 inches |
| Filament Designation: C-2r Average Life Ratures: 1000000 Filament Heavy Duty Service Rating: Not rated End Application: Arive, average, avion p-2, helicopter, cobra/attack, ah-1; Enttet Light Characteristic: Rati Votage Rating: 0.00 vols Votage Rating: 0.00 vols Vatage Rating: 0.01 vols Vatage Rating: 0.02 vols Vatage Rating: 0.02 vols | Wire Lead Length: |
| C-2° Average Life Rating In Hours: 100000 Filement Heav Daty Service Rating: Not rated End Leave Daty Service Rating: Not rated End Application: Avis rated to the cobravitation, and 1/4, sireraft, hawkeye e-2c; ta-4j aircraft; aircraft, c-2a (reprocured); helicopter, advance attack, ah-1] Entited Light Characteristic: Not rated Values Rating: Solo volts Watage Rating: Solo volts Base Servic: Virb leads, down Ball Servic: Virb leads, down Ball Servic: Virb leads, down Ball Designator: Rotal Designator: Rotal Design | 1.375 inches |
| Average Life Rating In Hours: 1000000 Filament Heavy Duty Service Rating: Not rated Ford Application: Aircard, wiking s-ds, aircard, tomcat-144; aircard, hawkeye e-2c; ta-4j aircard; aircard; o-2a (reprocured); helicopter, advance attack, ah-1y; aircard, orion p-3; helicopter, cobra/attack, ah-1j Emitted Light Characteristic: Rot Voltage Rating: 0.00 vols Watage Rating: 0.30 watis Bassyle: Victual (Light Characteristic: Totubul Viage Rating: 0.30 watis Bassyle: Victual (Light Transmission Characteristic: Totubuar) Bub Designator: Totapage Rating Oxido amperes Rated Average Life: Nava Avia coptable Aria coptable Point Rating Position: Nava Avia coptable Point Rating Position: Nava Nava Avia coptable Point Comment Nava | Filament Designation: |
| 10000.0 Filament Heavy Duty Service Rating: Not rated End Application: Aircraft, wiking s-3b; aircraft, tomcat f-14; aircraft, hawkeye e-2c; ts-4j aircraft; aircraft, c-2a (reprocured); helicopter, advance attack ah-1y; aircraft, coino p-3; helicopter, cobra/attack, ah-1j: Emitted Light Characteristic: Red Voltage Rating: S.000 volts Watage Rating: 0.300 watts Babe Style: Vitubus Designator: T. (tubular) Bub Style: T. (tubular) Bub Style: T. (tubular) Bub Apple Stoine T. (tubular) Bub Apple Stoine T. (tubular) Bub Apple Stoine Carcer Rating For Which Designed: T. (tubular) Burge Stoine: Apple Stoine: Apple Stoine: Apple Stoine: Apple Stoine: Name D' Mol Measure: Name Data Style: Stoine (Stoine): Apple Stoine: Apple Stoine: Dato (Stoine): | C-2r |
| Flament Heavy Duty Service Rating: Not rated End Application: Aircatd, viking s-3b, aircaft, tomcat 1-14; aircraft, hawkeyse -2c; ta-4] aircraft, aircraft, c-2a (reprocured); helicopter, advance attack, ah-14; aircraft, orion p-3; helicopter, oobra/attack, ah-19 Emitted Light Characteristic: Rott Voltage Rating: 5.000 volts Watage Rating: 3.000 volts Base Style: Vite leads, down Base Style: Yite leads, down Bub Ing Designator: Transparent Current Rating For Which Designed: Not agrees Rated Voltage Life: Not agrees Rated Voltage Life: Not agrees Rott Ord Measure Air agrees Rott Ord Measure Rott Ord Measure Rott Ord Measure Not agrees Rott Ord Measure Rott Ord Measure Not agrees Rott Ord Measure Not agrees Rott Ord Measure Not agrees Rott Ord Measure Not agrees <t< td=""><td>Average Life Rating In Hours:</td></t<> | Average Life Rating In Hours: |
| Not rated End Application: Air craft, viking s-3b; aircraft, tomcat f-14; aircraft, hawkeye s-2c; ta-4j aircraft, sicreaft, ciceptrocured; helicopter, advance attack, ah-1j Entited Light Characteristic: Entited Light Characteristic: Rod Voltage Rating: 3.000 volts Base Style: Voltage dating: Not voltads Base Style: Viculual) Buitted Light Characteristic: Totubal Didue State Buitted Transmission Characteristic: Totage Rating Note and State Buitted Transmission Characteristic: Totage Rating For Which Designed: Note and State Aire and State Rater State Rater State Rater State Rater State Rater State Rater State Buitter State Rater State < | 100000.0 |
| End Application: Aircraft, viking s-3b; aircraft, tomcat f-14; aircraft, hawkeye e-2c; ta-4j aircraft, aircraft, e-2a (reprocured); helicopter, advance attack, ah-1y; aircraft, orion p-3; helicopter, cobra/attack, ah-1j Emitted Light Characteristie: Red Voltage Rating: 5.000 volts Wattage Rating: 0.300 watts Base Style: Vitude Rating: 0.300 watts Babe Style: Vitude Name Bub Designator: T.3/4 Bub Light Transmission Characteristie: Tansparent Curent Rating For Which Designed: Aiova cograbile Hours Rated Verage Life: Nay acceptable Parting For Which Designed: Nay acceptable Parting Position: Nay acceptable Parting For Which Designed: Nay acceptable Parting Position: Nay acceptable Parting Position: Nay Nay Di Mode Massee: Nay Di Mode Massee: Nay Nay | Filament Heavy Duty Service Rating: |
| Aircraft, viking s-3b; aircraft, tomcat f-14; aircraft, hawkeye e-2c; ta-4j aircraft; aircraft, c-2a (reprocured); helicopter, advance attack, ah-1w; aircraft, orion p-3; helicopter, cobra/attack, ah-1j Emitted Light Characteristic: Red Voltage Rating: 0.000 volts Wattage Rating: 0.300 watts Base Style: Wire leads, down Bub Style: T dubulay Bub Designator: T-3/4 Bub Light Transmission Characteristic: Transparent Current Rating For Which Designed: Aircraft Ai | |
| ah-1w; aircraft, orion p-3; helicopter, cobra/attack, ah-1j Entited Light Characteristic: Red Voltage Rating: 5.000 volts Wattage Rating: 0.300 watts Base Style: Vire leads, down Bulb Style: T (tubular) Bulb Designator: T-3/4 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.600 ampres Rated Average Life: Hours Burning Position: Any acceptable Viral Na Uht Of Messure: | End Application: |
| Emitted Light Characteristic: Red Voltage Rating: 5.000 volts Wattage Rating: 0.300 watts Bate Style: Vire leads, down Bub Style: Virubular) Bub Designator: T.3/4 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.060 amperes Rated Average Life: Hours Sup Stotion: Any acceptable Chef Life: Na Unt Of Measure: - Pamiliarization: No | |
| Red Votage Rating: 5.000 volts Wattage Rating: 0.300 watts Base Style: Vittage Rating: Vittage Rating: Wittage Rating: Wittage Rating: Vittage Rating: Vittage Rating: Vittage Rating: Vittage Rating: Vittage Rating: Vittage Rating: Tayle Bub Designator: Tayle Bub Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0x060 amperes Rated Average Life: Hours Any acceptable Shelf Life: Na Uht Of Measure: Tayle Fomiliarization: | ah-1w; aircraft, orion p-3; helicopter, cobra/attack, ah-1j |
| Votage Rating:5.000 voltsWatage Rating:0.300 wattsBase Style:Wire leads, downBub Style:T (tubular)Bub Dosignator:T.3/4Bub Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.060 amperesRated Average Life:Anny acceptableSuring Position:Any acceptableNatDiff Measure:Pinilitarization:NatNatNatNatNatNatNational Market State S | Emitted Light Characteristic: |
| S.000 volts Wattage Rating: 0.300 watts Base Style: Wire leads, down Buib Style: T (tubular) Bulb Designator: T -3/4 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Sheff Life: N/a Unit Of Measure: - Demilitarization: No | Red |
| Watage Rating:0.300 watasBase Style:Vire leads, downBub Style:T (tubular)Bub Designator:T .3/4Bub Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.060 amperesRated Average Life:HoursSheff Life:Nay acceptableDist for Machine Life:NayDist for Machine Life:NayNayDist for Machine Life:NayNayDist for Machine Life:Nay <td< td=""><td>Voltage Rating:</td></td<> | Voltage Rating: |
| 0.300 wats Base Style: Vire leads, down Bulb Style: T (tubular) T (tubular) T-3/4 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: O.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | 5.000 volts |
| Base Style:Wire leads, downBulb Style:T (tubular)Bulb Designator:T-3/4Buls Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.00 amperesRated Average Life:HoursBurning Position:Any acceptableSheff Liffe:N/aDird Measure:TMaDird Measure:TNaDird Measure:NaNaSub State:NaNaSub State:Na <td< td=""><td>Wattage Rating:</td></td<> | Wattage Rating: |
| Wire leads, downBulb Style:T (tubular)Bulb Designator:T-3/4Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.060 amperesRated Average Life:HoursBurning Position:Any acceptableSheff Life:N/aUnt Of Measure:Pemilitarization:No | |
| Bub Style:T (tubular)Bulb Designator:T-3/4T-3/4Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.600 amperesRated Average Life:HoursBurning Position:Any acceptableShelf Life:NaDirt of Measure:Penilitarization:No | Base Style: |
| T (tubular) Bulb Designator: T-3/4 Fulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: O.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | |
| Bulb Designator:T-3/4Bulb Light Transmission Characteristic:FransparentCurrent Rating For Which Designed:0.060 amperesRated Average Life:HoursBurning Position:Any acceptableShelf Life:N/aDit of Measure:Demilitarization:No | - |
| T-3/4Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.060 amperesRated Average Life:HoursBurning Position:Any acceptableShelf Life:N/aUnit Of Measure:-Demilitarization:No | |
| Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Dint Of Measure: Pomilitarization: No | |
| Transparent Current Rating For Which Designed: 0.060 amperes Rated Average Life: Hours Hours Any acceptable Shelf Life: N/a Unit Of Measure: Houris No | T-3/4 |
| Current Rating For Which Designed: 0.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Pomilitarization: No | |
| 0.060 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | |
| Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | |
| Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | |
| Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | - |
| Any acceptable Shelf Life: N/a Unit Of Measure: Demilitarization: No | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No | - |
| N/a Unit Of Measure: Demilitarization: No | |
| Unit Of Measure: Demilitarization: No | |
| Demilitarization: No | |
| Demilitarization: No | Unit Of Measure: |
| No | |
| | |
| Fiig: | |
| | |
| A07900 | A07900 |