

View Online at <https://aerobasegroup.com/nsn/6240-00-155-7967>

Overall Length:

1.188 inches

Filament Designation:

C-2v

Light Output Rating:

0.860 lumens single rating

Average Life Rating In Hours:

1000.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Nimitz class cvn; tarawa class lha; I.P. Compressors; fire pumps; austin ship class lpd-4 amphibious transport docks; armored vehicle launch bridge (m60a1 & m48a5); low pressure (lp) air dehydrators; shipboard material handling equipment (mhe); supply class aoe; spruance class dd (963); helicopter, sea king h3; aircraft, hornet f/a-18; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg, search and rescue, hh-60j

Emitted Light Characteristic:

Colorless

Light Center Length:

0.625 inches

Voltage Rating:

14.400 volts

Wattage Rating:

1.440 watts

Features Provided:

Filament shielding and heat resistant glass

Base Style:

Miniature bayonet

Bulb Style:

T (tubular)

Bulb Designator:

T-3 1/4

Bulb Light Transmission Characteristic:

Transparent

Current Rating For Which Designed:

0.100 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07900