NSN 6240-00-155-8645

Incandescent Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-00-155-8645

Since: Filament Designation: 2-co8 Light Output Rating: 23100.000 lumens single rating Average Life Rating In Hours: 1000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vihite Light Center Length: 9.500 inches Votage Rating: 1000.00 volts Base Style: 1000.000 volts Base Style: Noguiscrew Bulb Style: Ps: (peer shape, straight neck) Bulb Designator: Ps: 52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Ary acceptable Sher Liff: No No Filie: Avarage Life: Avarage Life: Hours Burning Position: Ary acceptable Sherel Liffer <th>Overall Length:</th> <th></th>	Overall Length:	
Flament Designation: 2-co8 Light Output Rating: 23100.000 lumens single rating Average Life Rating In Hours: 1000.0 Filament Heavy Duty Service Rating: Not rated Emited Light Characteristic: Virite Light Conter Longth: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 volts Base Style: Nogul screw Bulb Style: Posefator: Pase2 Bulb Light Transmission Characteristic: Translucent Rated Average Life: Hours Signation: Pase1 Outool / 120v manufacturers standard Shef Life: Na Dird Measure: Na Demilatization: Na Fig:	-	
2-cc8 Light Cutput Rating: 23100.000 lumens single rating Average Life Rating In Hours: 1000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vihite Light Conter Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 volts Bate Style: Nogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Style: Ps-S2 Buld Light Transmission Characteristic: Translucent Current Rating For Which Designed: Avarage Life: Hours Station Date: Ost(Date): Ost(Date): Ost(Date): Nay acceptable Sherification Data: Ost(Data): Ost(Data): Ost(Data): Ost(Data): Ost(Data): Ost(Data): Ost(Data): Ost(Data): Ost(Data): <		
Lipht Output Rating: 23100.000 lumens single rating Average Life Rating In Hours: 1000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Light Center Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 volts Base Style: Not 2000 watts Base Style: Not 2000 watts Base Style: Ps (pars shape, straight neck) Bulb Style: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: A:33 ampres Rated Average Life: Any acceptable Specification Data: Offication Data: Outool-1200 manufacturers standard Sheft Life: Na Demiliarization: For		
23100.000 lurens single rating Average Life Rating In Hours: 1000.0 Filement Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vihite Light Center Length: 9,500 inches Voltage Rating: 120.000 volts Voltage Rating V		
Average Life Rating In Hours: 1000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Light Characteristic: 9.500 inches Voltage Rating: 120.000 volts Watage Rating: 1000.000 watts Base Style: Nogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: Ayas aceptable Burning Position: Anya aceptable Stol 1000/1-120v manufacturers standard Sheft Life: Na Ditol Measure: No Fig:		
1000.0 Flament Heavy Duty Service Rating: Not rated Enitted Light Characteristic: White Light Center Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 volts Base Style: Noto: Moyl screw Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Stroling Position: Any acceptable Specification Data: 04100-1200/manufacturers standard Sheff Life: Na Lift of Measure: Car Demilitarization: No Fig:		
Flament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Light Center Length: 9.500 Inches Votage Rating: 120.000 volts Wattage Rating: 1000.000 wolts Base Style: Mogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Distriction Data: 0x10 dott-120x manufacturers standard Shef Life: Na Unit Of Measure: r- Femilitarization: No Fig:		
Not rated Emitted Light Characteristic: White Light Center Length: 9.500 inches Voltage Rating: 1000.000 volts Wattage Rating: 1000.000 watts Base Style: 1000.000 watts Base Style: Nogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000/1-120V manufacturers standard Sheft Life: Na		
Enited Light Characteristic: White Light Center Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 outus Base Style: Mogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Optimication Data: Optimication Data: Optimication Data: Nat Shelf Life: Nat Formilatarization: Nat Formilatarization: Nat Formilatarization: Nat		
White Light Center Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 120.000 wolts Bub Style: Page as style: Mogul screw Bub Style: Ps (pear shape, straight neck) Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Specification Data: 08108-1000if-120x manufacturers standard Shelf Life: Na Lint Of Measure: r Femilitarization: Na Fig:		
Light Center Length: 9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 1000.000 watts Base Style: Mogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: Oki04:1000if-120v manufacturers standard Shelf Life: Na Formilitarization: Formilitarization: Formilitarization:		
9.500 inches Voltage Rating: 120.000 volts Wattage Rating: 1000.000 watts Base Style: Hogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Style: Ps (pear shape, straight neck) Bulb Light Transmission Characteristic: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Lift of Measure: F Demilitarization: No	Light Center Length:	
120.00 volts Wattage Rating: 1000.000 watts Base Style: Mogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Image: No Fig:		
Wattage Rating:1000.000 wattsBase Style:Mogul screwBulb Style:Ps (pear shape, straight neck)Bulb Designator:Ps-52Bub Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:8.333 amperesRated Average Life:HoursDesification Data:08108-1000if-120v manufacturers standardBuble 1 Life:N/aDesification Data:Int of Measure:NaFig:NoFig:No	Voltage Rating:	
1000.000 watts Base Style: Mogul screw Bulb Style: Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burls Position: Any acceptable Speficiation Data: 08108-1000if-120v manufacturers standard Meilt Life: N/a Dift of Measure: - Demilitarization: No Fig:	120.000 volts	
Base Style:Mogul screwBulb Style:Ps (pear shape, straight neck)Bulb Designator:Ps-52Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:8.333 amperesRated Average Life:HoursBurning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:NaDint of Measure:-Pomilitarization:NoFig:	Wattage Rating:	
Mogul screwBulb Style:Ps (pear shape, straight neck)Bulb Designator:Ps-52Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:8.333 amperesRated Average Life:HoursBurning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:N/aDint of Measure:Pomilitarization:NoFig:	1000.000 watts	
Bulb Style: Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: Iv/a Init Of Measure: Na Fig:	Base Style:	
Ps (pear shape, straight neck) Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mogul screw	
Bulb Designator: Ps-52 Bulb Light Transmission Characteristic: Translucent Translucent Current Rating For Which Designed: Ausar Rated Average Life: As33 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Bulb Style:	
Ps-52 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Ps (pear shape, straight neck)	
Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:8.333 amperesRated Average Life:HoursBurning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:N'aUnit Of Measure:NoFig:	Bulb Designator:	
Translucent Current Rating For Which Designed: 8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Ps-52	
Current Rating For Which Designed:8.333 amperesRated Average Life:HoursBurning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Bulb Light Transmission Characteristic:	
8.333 amperes Rated Average Life: Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Translucent	
Rated Average Life:HoursBurning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Current Rating For Which Designed:	
Hours Burning Position: Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	8.333 amperes	
Burning Position:Any acceptableSpecification Data:08108-1000if-120v manufacturers standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Rated Average Life:	
Any acceptable Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hours	
Specification Data: 08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Burning Position:	
08108-1000if-120v manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Any acceptable	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure: Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:		
A07900		
	A07900	