

View Online at <https://aerobasegroup.com/nsn/6240-00-183-0658>

**Overall Length:**

0.250 inches

**Wire Lead Length:**

1.000 inches

**Filament Designation:**

C-2r

**Light Output Rating:**

0.034 spherical candlepower single rating

**Average Life Rating In Hours:**

10000.0

**Filament Heavy Duty Service Rating:**

Not rated

**End Application:**

Forrestal class cv; missile, minuteman lgm-30; aircraft, strato fortress b-52; kidd class ddg; spruance class dd (963); fms - knox class ff; fms - aircraft, hawk eye e-2c; tarawa class lha; strategic weapon systems (poseidon and trident); consolidated targets

**Emitted Light Characteristic:**

Colorless

**Light Center Length:**

0.070 inches

**Voltage Rating:**

5.000 volts

**Wattage Rating:**

0.100 watts

**Features Provided:**

Preaged lamp

**Base Style:**

Wire leads, down

**Bulb Style:**

T (tubular)

**Bulb Designator:**

T-1

**Bulb Light Transmission Characteristic:**

Transparent

**Current Rating For Which Designed:**

0.020 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Specification Data:**

08108-6022 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07900