NSN 6240-00-222-9392

Cartridge Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-00-222-9392

| <u> </u> | |
|----------|---------------------------------------|
| | lorless |
| | irtridge Style: |
| | ort cylindrical |
| | rtridgelength: |
| | 265 inches |
| | rtridgediameter: |
| 0.3 | 330 inches |
| Pri | imary Lamp Type: |
| Glo | wo |
| Lię | ght Intensity Level: |
| Sta | andard |
| Ci | rcuit Voltage Rating In Volts: |
| Be | tween 105.000 and 125.000 |
| A٧ | erage Life Rating In Hours: |
| 30 | 00.0 |
| Ba | se Style: |
| Са | rtridge two pin polarized |
| Le | ns Light Transmission Characteristic: |
| Tra | ansparent |
| Fil | ling Gas Type: |
| Ne | on |
| Re | sistor Rating And Location: |
| 56 | .000 kilohms internal |
| Ra | ted Average Life: |
| Ho | urs |
| Ма | aterial: |
| Pla | astic lens |
| Ма | aterial: |
| Pla | astic lens |
| Sh | elf Life: |
| N/a | a |
| Un | it Of Measure: |
| | |
| De | militarization: |
| No | |
| Fii | g: |
| A0 | 7900 |