NSN 6240-00-246-5060



Incandescent Lamp - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6240-00-246-5060 **Overall Length:** 0.594 inches **Filament Designation:** C-2r **Light Output Rating:** 0.200 spherical candlepower single rating **Average Life Rating In Hours:** 500.0 **Filament Heavy Duty Service Rating:** Not rated **End Application:** Nguided missile launching system, mk26 (gmls); boilers, 1200 psi; chilled water a/c systems; fire pumps; I.P. Compressors; systems, 02n2; gun, 5-in./54 cal, mk-42 & 45; elevators, cargo/weapons; elevators, aircraft **Emitted Light Characteristic:** Colorless **Light Center Length:** 0.520 inches Voltage Rating: 2.500 volts Wattage Rating: 0.500 watts Base Style: Midget screw **Bulb Style:** T (tubular) **Bulb Designator:** T-1 3/4 **Bulb Light Transmission Characteristic:** Transparent **Current Rating For Which Designed:** 0.200 amperes Rated Average Life: Hours **Burning Position:** Any acceptable **Specification Data:** 08108-1767 manufacturers standard Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 6240-00-246-5060

Incandescent Lamp - Page 2 of 2



Fiig:

A07900