

View Online at <https://aerobasegroup.com/nsn/6240-00-270-4697>

**Overall Length:**

0.680 inches

**Filament Designation:**

C-2r

**Light Output Rating:**

0.220 spherical candlepower single rating

**Average Life Rating In Hours:**

500.0

**Filament Heavy Duty Service Rating:**

Not rated

**End Application:**

Fms-asroc launcher; helicopter, sea king h-3; systems, 02n2; elevators, aircraft; boilers, 1200 psi; stream (std, tensioned replenishment at sea method); chilled water a/c systems; fire pumps; I.P. Compressors; elevators, cargo/weapons; main feed pumps

**Emitted Light Characteristic:**

Colorless

**Light Center Length:**

0.500 inches

**Voltage Rating:**

2.500 volts

**Wattage Rating:**

0.500 watts

**Base Style:**

Midget screw

**Bulb Style:**

T (tubular)

**Bulb Designator:**

T-1 3/4

**Bulb Light Transmission Characteristic:**

Transparent

**Current Rating For Which Designed:**

0.200 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Specification Data:**

08108-1769 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07900