

View Online at <https://aerobasegroup.com/nsn/6240-00-295-1184>

Overall Length:

2.000 inches

Filament Designation:

C-6 and c-6

Light Output Rating:

32.000 spherical candlepower single rating and 3.000 spherical candlepower single rating

Average Life Rating In Hours:

200.0 and 5000.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Helicopter, uscg search and rescue, hh-60j; whidbey island class lsd; truck, fire/crash p2; forrestal class cv; helicopter, search and rescue, hh-60h; supply class aoe; nimitz class cvn; shipboard material handling equipment (mhe); wasp class lhd; helicopter, sea king h-3; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, advance attack, ah-1w; trident auxiliary systems

Emitted Light Characteristic:

Colorless

Light Center Length:

1.250 inches

Voltage Rating:

12.800 volts and 14.000 volts

Wattage Rating:

23.040 watts and 8.260 watts

Base Style:

Double contact bayonet candelabra indexing

Bulb Style:

S (straight side)

Bulb Designator:

S-8

Bulb Light Transmission Characteristic:

Transparent

Current Rating For Which Designed:

1.800 amperes and 0.590 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07900