

View Online at <https://aerobasegroup.com/nsn/6240-00-295-1184>

**Overall Length:**

2.000 inches

**Filament Designation:**

C-6 and c-6

**Light Output Rating:**

32.000 spherical candlepower single rating and 3.000 spherical candlepower single rating

**Average Life Rating In Hours:**

200.0 and 5000.0

**Filament Heavy Duty Service Rating:**

Not rated

**End Application:**

Helicopter, uscg search and rescue, hh-60j; whidbey island class lsd; truck, fire/crash p2; forrestal class cv; helicopter, search and rescue, hh-60h; supply class aoe; nimitz class cvn; shipboard material handling equipment (mhe); wasp class lhd; helicopter, sea king h-3; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, advance attack, ah-1w; trident auxiliary systems

**Emitted Light Characteristic:**

Colorless

**Light Center Length:**

1.250 inches

**Voltage Rating:**

12.800 volts and 14.000 volts

**Wattage Rating:**

23.040 watts and 8.260 watts

**Base Style:**

Double contact bayonet candelabra indexing

**Bulb Style:**

S (straight side)

**Bulb Designator:**

S-8

**Bulb Light Transmission Characteristic:**

Transparent

**Current Rating For Which Designed:**

1.800 amperes and 0.590 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07900