

View Online at <https://aerobasegroup.com/nsn/6240-00-643-0687>

**Overall Length:**

4.090 inches

**Filament Designation:**

2c-6

**Light Output Rating:**

1600.000 beam candlepower single rating

**Average Life Rating In Hours:**

800.0

**Filament Heavy Duty Service Rating:**

Not rated

**Light Beam Type:**

Flood

**End Application:**

Helicopter, mh-53e; aircraft, prowler ea-6b; landing craft air cushion (lcac); helicopter, carrier based asw, sh-60f; aircraft, c-2a (reprocured); helicopter, search and rescue, hh-60h; truck, fire/crash p8; shipboard material handling equipment (mhe); helicopter, advance attack, ah-1w; truck, fire/crash p2; 2320-01-442-1940, truck, cbt, (command bridge transporter)

**Emitted Light Characteristic:**

Colorless

**Voltage Rating:**

28.000 volts

**Wattage Rating:**

60.000 watts

**Base Style:**

Two contract lugs (not contact)

**Bulb Style:**

Par (parabolic, aluminized reflector)

**Bulb Designator:**

Par-46

**Bulb Light Transmission Characteristic:**

Transparent

**Light Intensity Distribution Feature:**

Parabolic reflector

**Current Rating For Which Designed:**

2.143 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Specification Data:**

08108-4578 manufacturers standard

**Specification Or Standard:**

I type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07900