

View Online at <https://aerobasegroup.com/nsn/6240-00-643-0687>

Overall Length:

4.090 inches

Filament Designation:

2c-6

Light Output Rating:

1600.000 beam candlepower single rating

Average Life Rating In Hours:

800.0

Filament Heavy Duty Service Rating:

Not rated

Light Beam Type:

Flood

End Application:

Helicopter, mh-53e; aircraft, prowler ea-6b; landing craft air cushion (lcac); helicopter, carrier based asw, sh-60f; aircraft, c-2a (reprocured); helicopter, search and rescue, hh-60h; truck, fire/crash p8; shipboard material handling equipment (mhe); helicopter, advance attack, ah-1w; truck, fire/crash p2; 2320-01-442-1940, truck, cbt, (command bridge transporter)

Emitted Light Characteristic:

Colorless

Voltage Rating:

28.000 volts

Wattage Rating:

60.000 watts

Base Style:

Two contract lugs (not contact)

Bulb Style:

Par (parabolic, aluminized reflector)

Bulb Designator:

Par-46

Bulb Light Transmission Characteristic:

Transparent

Light Intensity Distribution Feature:

Parabolic reflector

Current Rating For Which Designed:

2.143 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Specification Data:

08108-4578 manufacturers standard

Specification Or Standard:

I type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07900