

View Online at <https://aerobasegroup.com/nsn/6240-00-727-8573>

**Overall Length:**

4.090 inches

**Filament Designation:**

2c-6

**Light Output Rating:**

6000.000 beam candlepower single rating

**Average Life Rating In Hours:**

800.0

**Filament Heavy Duty Service Rating:**

Rough service

**End Application:**

Wasp class lhd; truck, fl (m10a); tarawa class lha; loader scoop; whidbey island class lsd; landing craft air cushion (lcac); tractor, full track; container, handler (dv-43); shipboard material handling equipment (mhe)

**Emitted Light Characteristic:**

Colorless

**Voltage Rating:**

28.000 volts

**Wattage Rating:**

60.000 watts

**Features Provided:**

Filament shielding

**Base Style:**

Two contract lugs (not contact)

**Bulb Style:**

Par (parabolic, aluminized reflector)

**Bulb Designator:**

Par-46

**Bulb Light Transmission Characteristic:**

Transparent

**Light Intensity Distribution Feature:**

Parabolic reflector

**Current Rating For Which Designed:**

2.300 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Specification Data:**

08108-4880 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07900