

View Online at <https://aerobasegroup.com/nsn/6240-00-752-2424>

Overall Length:

5.250 inches

Filament Designation:

2c-6

Light Output Rating:

32.000 beam candlepower single rating and 50.000 beam candlepower single rating

Average Life Rating In Hours:

300.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Pw/s: aircraft, t-39; fire pumps; truck, fire/crash p2; tarawa class lha; forrestal class cv; chassis, truck (tss); shipboard material handling equipment (mhe); nimitz class cvn; wasp class lhd; truck, fire/crash p-10

Emitted Light Characteristic:

White

Voltage Rating:

12.800 volts and 12.800 volts

Wattage Rating:

60.000 watts and 60.000 watts

Features Provided:

Filament shielding

Base Style:

Three contact lugs

Bulb Style:

Par (parabolic, aluminized reflector)

Bulb Designator:

Par-56

Bulb Light Transmission Characteristic:

Transparent

Light Intensity Distribution Feature:

Parabolic reflector

Current Rating For Which Designed:

4.200 amperes and 4.970 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Special Features:

500.000 hrs second filament average life rating

Specification Data:

08108-6015 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07900