

View Online at <https://aerobasegroup.com/nsn/6240-00-764-8237>

**Overall Length:**

0.375 inches

**Filament Designation:**

C-2r

**Light Output Rating:**

0.150 spherical candlepower single rating

**Average Life Rating In Hours:**

40000.0

**Filament Heavy Duty Service Rating:**

Not rated

**End Application:**

Jfms-asroc launcher; non-trident exterior communication; sonar signal processing sys, an/sqq-2 (v); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); deep submergence systems programs (dssp); tactical air opns module (an/tyq-(23)); tactical data system, an/uva-4(v); aircraft, eagle f-15; engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p); communications systems, an/wrr-7; aircraft, c-2a (reprocured); advanced air traffic contr. & land.Sys (atcals) 404I; helicopter, mh-53e

**Emitted Light Characteristic:**

Colorless

**Light Center Length:**

0.188 inches

**Voltage Rating:**

5.000 volts

**Wattage Rating:**

0.575 watts

**Features Provided:**

Filament shielding and heat resistant glass

**Base Style:**

Sub-midget flanged

**Bulb Style:**

T (tubular)

**Bulb Designator:**

T-1

**Bulb Light Transmission Characteristic:**

Transparent

**Current Rating For Which Designed:**

0.115 amperes

**Rated Average Life:**

Hours

**Burning Position:**

Any acceptable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07900