

View Online at <https://aerobasegroup.com/nsn/6240-00-764-8237>

Overall Length:

0.375 inches

Filament Designation:

C-2r

Light Output Rating:

0.150 spherical candlepower single rating

Average Life Rating In Hours:

40000.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Jfms-asroc launcher; non-trident exterior communication; sonar signal processing sys, an/sqq-2 (v); aircraft, (ac-130h, mc-130h, ec-130e, hc-130); deep submergence systems programs (dssp); tactical air opns module (an/tyq-(23)); tactical data system, an/uya-4(v); aircraft, eagle f-15; engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p); communications systems, an/wrr-7; aircraft, c-2a (reprocured); advanced air traffic contr. & land.Sys (atcals) 404I; helicopter, mh-53e

Emitted Light Characteristic:

Colorless

Light Center Length:

0.188 inches

Voltage Rating:

5.000 volts

Wattage Rating:

0.575 watts

Features Provided:

Filament shielding and heat resistant glass

Base Style:

Sub-midget flanged

Bulb Style:

T (tubular)

Bulb Designator:

T-1

Bulb Light Transmission Characteristic:

Transparent

Current Rating For Which Designed:

0.115 amperes

Rated Average Life:

Hours

Burning Position:

Any acceptable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07900