NSN 6240-00-824-0924

Incandescent Lamp - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6240-00-824-0924

Overall Length: 0.145 inches Wire Lead Length: 1.250 inches Filament Designation: C-2r Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a Unit Of Measure:	Overell Length
Wire Lead Length: 1.250 inches Filament Designation: C-2r Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Overall Length:
Filament Designation: C-2r Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Filament Designation: C-2r Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	•
Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Light Output Rating: 0.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	<u>-</u>
O.150 spherical candlepower single rating Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	- -
Average Life Rating In Hours: 40000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Emitted Light Characteristic: Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Colorless Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Light Center Length: 0.050 inches Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	_
Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	0.0.0.000
Voltage Rating: 5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
5.000 volts Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Wattage Rating: 0.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
O.575 watts Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: O.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Features Provided: Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Preaged lamp Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Base Style: Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Wire leads, down Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Bulb Style: T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	•
T (tubular) Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Wire leads, down
Criticality Code Justification: Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	•
Cbbl Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	
Bulb Designator: T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Criticality Code Justification:
T-1 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Cbbl
Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Bulb Designator:
Transparent Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	T-1
Current Rating For Which Designed: 0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Bulb Light Transmission Characteristic:
0.115 amperes Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Transparent
Rated Average Life: Hours Burning Position: Any acceptable Shelf Life: N/a	Current Rating For Which Designed:
Hours Burning Position: Any acceptable Shelf Life: N/a	0.115 amperes
Burning Position: Any acceptable Shelf Life: N/a	Rated Average Life:
Any acceptable Shelf Life: N/a	Hours
Shelf Life: N/a	Burning Position:
N/a	Any acceptable
. ,	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

NSN 6240-00-824-0924

Incandescent Lamp - Page 2 of 2



Demilitarization:

No

Fiig:

A07900