

View Online at <https://aerobasegroup.com/nsn/6240-00-877-3405>

Overall Length:

2.000 inches

Filament Designation:

Cc-6 and c-2v

Light Output Rating:

32.000 spherical candlepower single rating and 6.000 spherical candlepower single rating

Average Life Rating In Hours:

400.0 and 1000.0

Filament Heavy Duty Service Rating:

Not rated

End Application:

Otruck, fire/crash p8; aircraft, c-2a (reprocured); shipboard material handling equipment (mhe); fire pumps; tow tractor, aircraft mb2; truck, fire/crash p19; aircraft, t-39; helicopter, mh-53e; truck, fire/crash p2

Emitted Light Characteristic:

Colorless

Light Center Length:

1.250 inches

Voltage Rating:

28.000 volts

Wattage Rating:

26.040 watts and 26.320 watts

Base Style:

Double contact bayonet candelabra indexing

Bulb Style:

S (straight side)

Bulb Designator:

S-8

Bulb Light Transmission Characteristic:

Transparent

Current Rating For Which Designed:

Between 0.930 amperes and 0.940 amperes

Rated Average Life:

Hours

Burning Position:

Base down to horizontal

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07900