NSN 6240-00-901-8612

Incandescent Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-00-901-8612

Overall Length: 4.500 inches Filament Designation: Cc-6 Light Output Rating: 6100.000 lumens single rating Average Life Rating In Hours: 2000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic, aluminized reflector) Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 0x104 Measure: va Duit Of Measure: <th>4.500 inches Filament Designation: Cc-6</th> <th></th>	4.500 inches Filament Designation: Cc-6	
Cr-6 Light Output Rating: 6100.000 lumens single rating Average Life Rating In Hours: 2000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Para64 Burb Light Transmission Characteristic: Current Rating Position: Parabolic reflector Burbing Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Link of Measure: Init of Measure: Na Specification Data: Fig:	Cc-6	
Cr-6 Light Output Rating: 6100.000 lumens single rating Average Life Rating In Hours: 2000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Para64 Burb Light Transmission Characteristic: Current Rating Position: Parabolic reflector Burbing Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Link of Measure: Init of Measure: Na Specification Data: Fig:	Cc-6	
6100.000 lumens single ratingAverage Life Rating in Hours:2000.0Filament Heavy Duty Service Rating:Not ratedEmitted Light Characteristic:ColorlessVoltage Rating:0.022 voltsWattage Rating:300.000 wattsBase Style:Mogul end prongBulb Style:Par (parabolic, aluminized reflector)Bulb Designator:Par-64Bulb Light Transmission Characteristic:TransparentLight Intensity Distribution Feature:Parabolic reflectorCurrent Rating For Which Designed:6.600 amperesRated Average Life:HoursBase down to horizontalSpecification Data:09108-q6-64par64-3p manufacturers standardShelf Life:N/aUnit Of Measure:NaFig:NoFig:	Light Output Rating:	
6100.000 lumens single ratingAverage Life Rating in Hours:2000.0Filament Heavy Duty Service Rating:Not ratedEmitted Light Characteristic:ColorlessVoltage Rating:0.022 voltsWattage Rating:300.000 wattsBase Style:Mogul end prongBulb Style:Par (parabolic, aluminized reflector)Bulb Designator:Par-64Bulb Light Transmission Characteristic:TransparentLight Intensity Distribution Feature:Parabolic reflectorCurrent Rating For Which Designed:6.600 amperesRated Average Life:HoursBase down to horizontalSpecification Data:09108-q6-64par64-3p manufacturers standardShelf Life:N/aUnit Of Measure:NaFig:NoFig:		
Average Life Rating in Hours: 2000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.00 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q-6-64par64-3p manufacturers standard Sheff Life: N/a Lift of Measure: Tot of Measure: No Hours <th>6100.000 lumens single rating</th> <th></th>	6100.000 lumens single rating	
2000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Colorless Voltage Rating: 0.022 volts Wattage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Base Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Parabolic reflector Current Rating For Which Designed: Action any press Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: T No Fig:		
Not rated Emitted Light Characteristic: Coloriess Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Sheff Life: N/a Unit Of Measure: Fig:		
Not rated Emitted Light Characteristic: Coloriess Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Sheff Life: N/a Unit Of Measure: Fig:	Filament Heavy Duty Service Rating:	
Colorless Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Base down to horizontal Specification Data: 0.8108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit of Measure: - Foemilitarization: No Fig:		
Voltage Rating: 0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 0x108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Fig:	Emitted Light Characteristic:	
0.022 volts Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: - Demilitarization: No	-	
Wattage Rating: 300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Voltage Rating:	
300.000 watts Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.022 volts	
Base Style: Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Wattage Rating:	
Mogul end prong Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	300.000 watts	
Bulb Style: Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Base Style:	
Par (parabolic, aluminized reflector) Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mogul end prong	
Bulb Designator: Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Bulb Style:	
Par-64 Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Par (parabolic, aluminized reflector)	
Bulb Light Transmission Characteristic: Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Bulb Designator:	
Transparent Light Intensity Distribution Feature: Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Par-64	
Light Intensity Distribution Feature:Parabolic reflectorCurrent Rating For Which Designed:6.600 amperesRated Average Life:HoursBurning Position:Base down to horizontalSpecification Data:08108-q6-64par64-3p manufacturers standardShelf Life:N/aUnit Of Measure:NoFig:	Bulb Light Transmission Characteristic:	
Parabolic reflector Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Transparent	
Current Rating For Which Designed: 6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Dit Of Measure: Fig:	Light Intensity Distribution Feature:	
6.600 amperes Rated Average Life: Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Parabolic reflector	
Rated Average Life:HoursBurning Position:Base down to horizontalSpecification Data:08108-q6-64par64-3p manufacturers standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Current Rating For Which Designed:	
Hours Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Vnit Of Measure: Demilitarization: No Fig:	6.600 amperes	
Burning Position: Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Rated Average Life:	
Base down to horizontal Specification Data: 08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hours	
Specification Data:08108-q6-64par64-3p manufacturers standardShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Burning Position:	
08108-q6-64par64-3p manufacturers standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Base down to horizontal	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:	
N/a Unit Of Measure: Demilitarization: No Fiig:	08108-q6-64par64-3p manufacturers standard	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:		
-	No	
A07900	Fiig:	
A01300	A07900	