## NSN 6240-01-235-2604

Incandescent Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-01-235-2604

| Overall Length:   |
|---|
| 0.706 inches  |
| Light Output Rating:  |
| 1.500 spherical candlepower single rating   |
| Average Life Rating In Hours:   |
| 40.0  |
| Filament Heavy Duty Service Rating:   |
| Not rated   |
| Emitted Light Characteristic:   |
| Infrared  |
| Voltage Rating:   |
| 3.500 volts   |
| Wattage Rating:   |
| 2.450 watts   |
| Base Style:   |
| Midget grooved  |
| Bulb Style:   |
| T (tubular)   |
| Bulb Designator:  |
| T2  |
|   |
| Bulb Light Transmission Characteristic:   |
| Bulb Light Transmission Characteristic: Transparent   |
| _   |
| Transparent   |
| Transparent  Current Rating For Which Designed:   |
| Transparent  Current Rating For Which Designed:  0.700 amperes  |
| Transparent  Current Rating For Which Designed:  0.700 amperes  Rated Average Life:   |
| Transparent  Current Rating For Which Designed:  0.700 amperes  Rated Average Life:  Hours  |
| Transparent  Current Rating For Which Designed:  0.700 amperes  Rated Average Life:  Hours  Burning Position:   |
| Transparent  Current Rating For Which Designed:  0.700 amperes  Rated Average Life:  Hours  Burning Position:  Horizontal and vertical anode up   |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features:   |
| Transparent  Current Rating For Which Designed:  0.700 amperes  Rated Average Life:  Hours  Burning Position:  Horizontal and vertical anode up  Special Features:  Replacement lamp; for halogen retinoscope, 3.5 volt   |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features: Replacement lamp; for halogen retinoscope, 3.5 volt  Shelf Life:  |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features: Replacement lamp; for halogen retinoscope, 3.5 volt  Shelf Life: N/a                                      |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features: Replacement lamp; for halogen retinoscope, 3.5 volt  Shelf Life: N/a                                      |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features: Replacement lamp; for halogen retinoscope, 3.5 volt  Shelf Life: N/a  Unit Of Measure:                    |
| Transparent  Current Rating For Which Designed: 0.700 amperes  Rated Average Life: Hours  Burning Position: Horizontal and vertical anode up  Special Features: Replacement lamp; for halogen retinoscope, 3.5 volt  Shelf Life: N/a  Unit Of Measure:  Demilitarization: |