NSN 6240-01-344-5453

Incandescent Lamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6240-01-344-5453

4.000 incluss Filament Designation: C, c-7a Light Output Rating: 152.000 lumons single rating Average Life Rating In Hours: 4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vihite Voltage Rating: 120.000 volts Watage Rating: 20.000 volts Base Style: Medium screw skitted Base Style: Medium screw skitted Buib Designator: C-11 Buib Designator: Current Rating For Which Designed: Outfor amperes Rated Average Life: Hours Hours Special Features: Nava screptable Special Features: Navie: Navie: Navie: Special Features: Navie: Did Measure: Navie: Did Measure: Navie: Special Features: Navie: <td< th=""><th>Overall Length:</th></td<>	Overall Length:
C, c-7a Light Output Rating: 152.000 lumens: single rating Average Life Rating In Hours: 4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vhite Voltage Rating: 120.000 volts Wattage Rating: 20.000 volts Wattage Rating: 20.000 volts Base Style: Medium screw skirled Bulb Style: F (flame) Criticality Code Justification: Feat Bulb Designator: Criticality Code Justification: Franslucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vait-miser Shoff Life: Na Unit Of Measure: - Femiliter/Lation:	4.000 inches
Light Output Rating: 152.000 lumens single rating Average Life Rating In Hours: 4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Vottage Rating: 120.000 volts Watage Rating: 20.000 volts Watage Rating: 20.000 volts Base Style: Medium screw skirted Buils Style: F (flame) Criticality Code Justification: Feat Bub Designator: C-11 Bub Light Transmission Characteristic: Translucent Current Rating For Which Designed: Average Life: Hours Burning Position: Any acceptable Special Features: Vat-miser Mat-miser Special Features: Vat Na Data Contexteristic: Special Features: Vat Na Data Contexteristic Data Contexteristi	Filament Designation:
152.00 lumens single rating Average Life Rating In Hours: 4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: Vihite Voltage Rating: 120.000 volts Vattage Rating: 20.000 volts Vattage Rati	C, c-7a
Average Life Rating In Hours: 4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Voltage Rating: 120.000 volts Vattage Rating: 120.000 volts Vattage Rating: 120.000 volts Vattage Rating: 120.000 volts Pase Style: Nedium screw skitted Bub Style: F (flame) Criticality Code Justification: Feat Bub Designator: Criti Criticality Code Justification: Feat Bub Designator: Criticality Code Justification: Feat Bub Light Transmission Characteristic: Translucent Current Rating For Which Designed: Nate Average Life: Any acceptable Special Features: Vatt.miser Shefi Life: Natt.miser Shefi Life: Natt.miser Current Rating For Which Reser: Current Rating For Which Reser: Natt.miser Shefi Life: Natt.miser Part. P	Light Output Rating:
4000.0 Filament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Voltage Rating: 120.000 volts Wattage Rating: 20.000 volts Wattage Rating: 20.000 volts Base Style: Medium screw skirted Balb Style: F (flame) Criticality Code Justification: Feat Bub Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vatt-miser Sheff Life: N/a Unit Of Measure: Image: Pamilitarization:	152.000 lumens single rating
Flament Heavy Duty Service Rating: Not rated Emitted Light Characteristic: White Voltage Rating: 120.000 volts Wattage Rating: 20.000 volts Wattage Rating: 20.000 volts Base Style: Modium screw skinted Bulb Style: F (flame) Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vata Uit Of Measure: Vat Die Life: Na Die Life: Na Die Life: Na	Average Life Rating In Hours:
Not rated Entited Light Characteristic: White Voltage Rating: 120.000 volts Wattage Rating: 20.000 watts Base Style: Not rated Style: Not for any strinted Bub Style: F (flame) Criticality Code Justification: Feat Bub Designator: C-11 Bub Light Transmission Characteristic: Translucent Current Rating For Which Designed: 10.107 amperes Rated Average Life: Hours Superial Features: Vartimiser Superial Features: Vartimiser Superial Features: Native Superial Features: Native Superial Features: Native Superial Features: Native Did I Measure: Image: Native Diminitizzation: No	4000.0
Enited Light Characteristic: White Voltage Rating: 120.000 volts Wattage Rating: 20.000 watts Base Style: Hedium screw skinted Bub Style: F (flame) Criticality Code Justification: Feat Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vatt-miser Shef Life: Na Dit of Measure: ** Pinilitarization: **	Filament Heavy Duty Service Rating:
White Voltage Rating: 120.000 volts Wattage Rating: 20.000 watts Base Style: Medium screw skirted Bub Style: F (flame) Crticality Code Justification: Feat Bulb Designator: Cr11 Bub Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vatt-miser Nat Vat Mate Dirt of Measure: r- Pomilitarization:	Not rated
Voltage Rating:120.000 voltsWattage Rating:20.000 wattsBase Style:Medium screw skirtedBuib Style:F (flame)Criticality Code Justification:FeatBulb Designator:C-11Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:0.167 amperesRated Average Life:HoursBurning Position:Any acceptableSpecial Features:Vatt-miserNatDinf f Measure:Image Rated Average Life:NatDinf Measure:NatDinf Measure:Image Rated R	Emitted Light Characteristic:
120.000 volts Wattage Rating: 20.000 watts Base Style: Medium screw skirted Bulb Style: F (flame) Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vatt-miser Shelf Life: N/a Unit Of Measure: r Pomiltarization: No	White
Wattage Rating:20.000 wattsBase Style:Medium screw skirtedBulb Style:F (flame)Criticality Code Justification:FeatBulb Designator:C-11Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:0.167 amperesRated Average Life:HoursSpecial Features:Vatt-miserShelf Life:NaDint of Measure:Demiltarization:No	Voltage Rating:
20.000 watts Base Style: Medium screw skirted Bulb Style: F (flame) Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: O.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vatt-miser Nat-miser Inter Compatibility Designet Compatibilit	120.000 volts
Base Style: Medium screw skirted Bulb Style: F (flame) Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Special Features: Vatt-miser Fuel Life Vatt-miser Dit of Measure: Imit of Measure:	Wattage Rating:
Medium screw skirted Bulb Style: F (flame) F (flame) Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: O.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit of Measure:	20.000 watts
Bulb Style:F (flame)Criticality Code Justification:FeatBulb Designator:C-11Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:0.167 amperesRated Average Life:HoursBurning Position:Any acceptableSpecial Features:Watt-miserShelf Life:N/aDint of Measure:Pomilitarization:No	Base Style:
F (flame) Criticality Code Justification: Feat Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: O.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vatt-miser Shelf Life: Na Unit of Measure: - Demiltarization: No	Medium screw skirted
Criticality Code Justification: Feat Bulb Designator: C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: O.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vatt-miser Shelf Life: N/a Unit Of Measure: - Demilitarization:	Bulb Style:
FeatBulb Designator:C-11Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:0.167 amperesRated Average Life:HoursBurning Position:Any acceptableSpecial Features:Watt-miserShelf Life:N/aUnit Of Measure:Demilitarization:No	F (flame)
Bulb Designator:C-11Bulb Light Transmission Characteristic:TranslucentCurrent Rating For Which Designed:0.167 amperesRated Average Life:HoursBurning Position:Any acceptableSpecial Features:Watt-miserShelf Life:NaUnit Of Measure:Demilitarization:No	Criticality Code Justification:
C-11 Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Feat
Bulb Light Transmission Characteristic: Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vatt-miser Sheff Life: N/a Dint Of Measure: Pomilitarization: No	Bulb Designator:
Translucent Current Rating For Which Designed: 0.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Vatt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	C-11
Current Rating For Which Designed:0.167 amperesRated Average Life:HoursBurning Position:Any acceptableSpecial Features:Watt-miserShelf Life:N/aUnit Of Measure:Demilitarization:No	Bulb Light Transmission Characteristic:
0.167 amperes Rated Average Life: Hours Burning Position: Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Translucent
Rated Average Life:HoursBurning Position:Any acceptableSpecial Features:Vatt-miserShelf Life:N/aUnit Of Measure:Demilitarization:No	Current Rating For Which Designed:
Hours Burning Position: Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.167 amperes
Burning Position: Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Rated Average Life:
Any acceptable Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hours
Special Features: Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Burning Position:
Watt-miser Shelf Life: N/a Unit Of Measure: Demilitarization: No	Any acceptable
Shelf Life: N/a Unit Of Measure: Demilitarization: No	
N/a Unit Of Measure: Demilitarization: No	
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	
Demilitarization: No	Unit Of Measure:
No	
File	
	Fiig:
A07900	A07900