NSN 6250-01-347-4692

Lamp Ballast - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6250-01-347-4692

| Terminal Quantity: |
|--|
| 6 |
| Terminal Type: |
| Wire lead |
| Overall Length: |
| 9.500 inches |
| Overall Height: |
| 1.562 inches |
| Overall Width: |
| 2.375 inches |
| Mounting Hole Diameter: |
| Any acceptable |
| Mounting Hole Quantity: |
| 4 |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Center To Center Distance Between Mounting Holes Along Length: |
| 8.906 inches |
| Center To Center Distance Between Mounting Holes Along Width: |
| Any acceptable |
| Mounting Method: |
| Holes |
| Lamp Accommodation Quantity: |
| 3 |
| Lamp Wattage Rating In Watts: |
| 17.0 and 25.0 and 32.0 and 40.0 |
| Current Rating In Amps: |
| 0.720 or 0.750 or 0.780 |
| Voltage Rating: |
| 120.0 volts |
| Power Factor Characteristic: |
| High |
| Starting Characteristic: |
| Rapid |
| Starter: |
| Not required |
| Terminal Location And Quantity: |
| · · · · · · · · · · · · · · · · · · · |
| 2 one end and 4 other end |

T-8

NSN 6250-01-347-4692

Lamp Ballast - Page 2 of 2

Fiig: T316-c



| Lamp Type Accommodated: |
|--|
| Energy efficient |
| Environmental Attribute Code: |
| Energy efficient - femp - lighting - fluorescent ballasts |
| Special Features: |
| Used w/265 ma 4 ft lg lamp, fluorescent; will operate one or two lamps |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |