NSN 6250-01-348-5324

Lamp Ballast - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6250-01-348-5324

| Terminal Quantity: |
|--|
| 7 |
| Terminal Type: |
| Wire lead |
| Overall Length: |
| 3.938 inches |
| Overall Height: |
| 2.812 inches |
| Overall Width: |
| 3.562 inches |
| Mounting Hole Quantity: |
| 4 |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Center To Center Distance Between Mounting Holes Along Length: |
| 3.500 inches |
| Mounting Method: |
| Holes |
| Lamp Accommodation Quantity: |
| 1 |
| Lamp Wattage Rating In Watts: |
| 100.0 |
| Current Rating In Amps: |
| 50.550 or 0.600 or 0.700 or 1.200 |
| Voltage Rating: |
| 120.0 volts |
| Power Factor Characteristic: |
| High |
| Starting Characteristic: |
| Preheat |
| Starter: |
| Required |
| Terminal Location And Quantity: |
| 5 one end and 2 other end |
| Bulb Designator: |
| S-54 |
| Lamp Type Accommodated: |
| Energy efficient |
| Special Features: |

Used w/high pressure sodium lamps; ansi s-54; constant wattage autotransformer; includes core and coil; capacitor and all purpose mtg brkt; rated for 208, 240, and 277 vac

NSN 6250-01-348-5324

Lamp Ballast - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T316-c