

| Lamp Ballast - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/6250-01-352-9996 |
| Terminal Quantity: |
| 8 |
| Terminal Type: |
| Wire lead |
| Overall Length: |
| 14.312 inches |
| Overall Height: |
| 2.625 inches |
| Overall Width: |
| 3.188 inches |
| Mounting Hole Quantity: |
| 4 |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.0 hertz |
| Center To Center Distance Between Mounting Holes Along Length: |
| 13.750 inches |
| Center To Center Distance Between Mounting Holes Along Width: |
| 2.000 inches |
| Mounting Method: |
| Holes |
| Lamp Accommodation Quantity: |
| 1 |
| Lamp Wattage Rating In Watts: |
| 116.0 |
| Current Rating In Amps: |
| 0.560 |
| Voltage Rating: |
| 277.0 volts |
| Power Factor Characteristic: |
| High |
| Starting Characteristic: |
| Rapid |
| Starter: |
| Not required |
| Terminal Location And Quantity: |
| 4 each end |
| Bulb Designator: |
| T-12 |
| Lamp Type Accommodated: |
| Energy efficient |
| |

NSN 6250-01-352-9996

Lamp Ballast - Page 2 of 2



Special Features:

Used w/1500 ma 4 ft lg lamp, fluorescent

Reference Number Differentiating Characteristics:

As differentiated by features

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T316-c