

View Online at <https://aerobasegroup.com/nsn/6350-01-097-0128>

Hole Diameter:

Between 0.260 inches and 0.270 inches

Mounting Type:

Bracket

Discharge Connection Type:

Weep hole

Overall Length:

9.062 inches

Overall Width:

5.125 inches

Current Type:

Dc

Mounting Hole/stud Quantity:

2

Environmental Protection:

Weather resistant

End Application:

40liver perry class ffg; kidd class ddg; spruance class dd (963); wasp class lhd; arleigh burke class ddg; ticonderoga class cg (47);
forrestal class cv; nimitz class cvn; virginia class cgn (41); tarawa class lha; fms-build frigates class ships

Housing Material:

Aluminum, die cast or zinc

Internal Battery Accommodation:

Not included

Current Rating In Amps:

0.25

Inclosure Feature:

Watertight

Operation Method:

Electrical

Loudness Level In Decibels:

97 db at 10 ft at full volume

Sound Projector Quantity:

1

Sound Projector Type:

Diaphragm and trumpet

Mounting Bracket:

Provided

Sound Unit Type:

Single

Projector Type:

Straight

Projector Quantity:

1

Sound Signal Direction Quantity:

1

Product Name:

Horn, firing alarm

Voltage In Volts:

24.0

Special Features:

Adjustable loudness volume; distance between mounting holes 4.500 in. Nom

Surface Treatment:

Enamel, gray

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T104-e