

View Online at <https://aerobasegroup.com/nsn/6515-01-491-4633>

**Overall Length:**

7.000 inches

**Overall Height:**

1.500 inches

**Overall Width:**

3.000 inches

**Current Type:**

Dc

**Product Name:**

Pacemaker cardiac dc 9v 7" o/a lg 3"w 1.5"h w/hd case

**Voltage In Volts:**

9.0

**Special Features:**

External, single chamber, temporary, designed to provide temporary r-wave inhibited or asynchronous pacing for emergency, prophylactic, and pre or post operative patient management; includes adjustable rate, output, and sensing controls; pulse rate of 30-180 ppm, +/-5%, 80-90 to 450 ppm rapid atrial pacing; pulse width 1.5 to 1.8ms, +/-0.2 ms; output of .1-20 ma or .2-12 v +/- 15%; refractor period of 250 to 300 ms after pacing stimulus; 150 ms after pacing event +/- 30 ms; sensitivity of 0.5 to 1.0-12 to 20 mv, +/- 30%; touch controls; aai and a00 mode; push release lead connectors for patient cable pins or standard lead wires; stainless steel metal parts; capable of 30 days continuous operation; protected against defibrillator countershock to 400-500 joules; low battery condition indicator of sensing, pacing, and battery status; protected off control; provisioned in accordance w/mil-d-42048

**Supplementary Features:**

2supplied in hard carrying case with one pacemaker, 9 v alkaline or lithium battery, w straps (1 body one arm, hook and loop closure); one patient cable; 1 physician's manual; pacer is contained in a plastic housing and weighs approx 10 oz with battery; conforms to applicable requirements of a nationally recognized standard for the safety of medical equipment of the issue in effect on the date of solicitation and approved as conforming to standard by independent nationally recognized testing lab

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T133-f