

View Online at <https://aerobasegroup.com/nsn/6515-01-560-7883>

**Overall Height:**

225.0 millimeters

**Overall Width:**

148.0 millimeters

**Current Type:**

Ac

**Portability:**

Portable

**Product Name:**

Alaris gp volumetric pump

**Voltage In Volts:**

9.6

**Special Features:**

For acute and sub-acute applications. Infusion rate range: 1-1200 ml/h. Vtbi range primary: to 10000 ml. Vi range: 1 ml to 50000 ml. Volumetric accuracy: plus/minus 5 percent (). Mechanism: four finger displacement peristaltic. Display: mono (240 x 240) pixels. Free flow protection (alaris safety clamp). Kvo rates: 5 ml/h or set infusion rate if lower. Occlusion setting: 3 levels from I2, I5, I8 (factory default I5). Battery type: rechargeable nimh 9.6 v 2.4 ah . Battery run time: operates for 4 hr from full charge at 125 ml/h. Recharge time: 2 1/2 hrs from discharge to 95 percent charge. Electrical protection: class i, type cf (defibrillation proof). Ac power requirements: 100-230 vac, 50-60hz (). Dimensions: 148m (w) x 225mm(h) x 148mm(d) . Weight: 2.5kg.

**Frequency In Hertz:**

50.0 or 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T133-f