

View Online at <https://aerobasegroup.com/nsn/6525-00-853-8121>

**Mounting Type:**

Stationary

**Drive Type:**

Motor

**Accessory Components And Quantity:**

Photo-timing circuit 1, compression device 1, multidiaphragm adjustable radiographic cone 1, control /separate kilovoltage/for fluoroscopic kilovoltage 1, footrest 1, milliampere-second meter 1, spot-film change-over device 1, mylographic support patient 1, shoulder support 1

**Design Type:**

Stationary

**Operation Method:**

Automatic

**Control Type:**

Vertical

**Tube Quantity:**

1 and 1

**Electric Power Rating:**

65000.0 watts

**Tube Type:**

Double focus, rotating anode radiographic and double focus, rotating anode fluoroscopic

**Table Type:**

Tilting

**Rectification Type:**

Full-wave

**Err Default:**

Err default

**Tube Cooling Method:**

Air and air

**Tube Mounting Type:**

Tube stand and table

**Tube Stand Mounting Type:**

Overhead

**Err Default:**

Err default

**Err Default:**

Err default

**Radiographic Timer Type:**

Exposure

**Err Default:**

Err default

**Transformer Rectification Method:**

Electron tube

**Transformer Output Capacity:**

500 ma at 125 kv peak, 300 ma at 150 kv peak

**Err Default:**

Err default

**Err Default:**

Err default

**Err Default:**

Err default

**Err Default:**

Err default

**Product Name:**

X-ray apparatus radiogr-fluoroscopic 500ma 150pkv 230v 60hz ac

**Voltage In Volts:**

190.0 and 250.0

**Phase:**

Single

**Special Features:**

Requisition should state whether high-speed incerts are required

**Frequency In Hertz:**

60.0

**Supplementary Features:**

Requisition should state floor-loading capacity, ceiling strength and height, wall and floor construction (concrete, wood, etc), electrical supply and capacity, diagram of room indicating dimensions, compatability w/existing facilities, whether or not contractor installation service is required, and whether high-speed incerts are required

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T140-c