

View Online at <https://aerobasegroup.com/nsn/6525-01-220-5079>

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Operational Direction:

Left-hand or right-hand

Drive Type:

Roller

Tank Capacity:

7.00 gallons

Film Accommodation Type:

Roll

Tank Material:

Plastic

Replenisher Solution Tank Quantity:

2

Integral Replenisher Solution Pump:

Included

Product Name:

Processing machine rad film table top: compact120/230v50/60hz ac

Exterior Container Weight:

325.00 pounds

Voltage In Volts:

120.0 and 230.0

Exterior Container Cubic Measure:

14.00 cubic feet

Exterior Container Quantity:

1

Phase:

Single

Special Features:

90 sec processing; incl film feeding station, film transport system, film processing sect. W/tanks; solution replenishment sys w/14gal tanks; film dryer sect.; controls including developing temp control, temp indicator and over temp safety thermostat; automatic standby mode, water saver conversion kit, recirculation pump, mounting hardware and a 30 gal water tank for continuous processing of x-ray film using not more than 30 gal of water every 8 hrs & daylight loading device; roller type transport system picks up and transports mixed size film at nom rate of 230 shs of 35 by 43 cm film per hr or a rate of 350 shs of 35 by 43 cm film per hr in the rapid mode; for developing, fixing, washing and drying all standard brands of medical radiographic film manufactured for rapid automatic processing

Unit Of Issue Cube:

11.00 cubic feet

Unit Of Issue Weight:

265.00 pounds

Shelf Life:

N/a

Unit Of Measure:

Fig:

T150-c