

View Online at <https://aerobasegroup.com/nsn/6525-01-426-6753>

Product Name:

Ct auto injector system

Special Features:

Memory: 12 pre-stored protocols with up to 4 phases per protocol. Interphase delay: 0-255 secs in 1 sec increments; scan delay: 0-99 secs in 1 sec increments w/audible alarm; pressure limit: 25-300 psi in 50 psi increments; flow rate: 0.1-7.2 ml/sec with 200 ml syringe system and 0.1 to 4.9 ml/sec with 125 ml syringe system. Volume: 1-200 ml in 1 ml increments; fill speed: approx. From 2-7.2 ml/sec; syringe heater: blanket type...Maintains pre-heated contrast at 37 degrees c.

General Description:

Consists of: operator console, 1ea; injector powerhead, 1 ea; electronics power cabinet; remote ct auto injector stand, 1ea; 200 ml front loading system, 1 ea; 125 ml breach loading system, 1 ea; operating software; tech manuals; and a standard cable set consisting of: a 7 ft. Power cord, a 50 ft. Console cable, and a 50 ft. Injector head cable. The system has 110/220 vac, 50/60 hz capability but the requisitioner must state their requirements so the correct power cord can be requested for the system.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No