## NSN 6605-00-224-3394

Drift Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6605-00-224-3394

| Overall Length:  |
|--|
| 7.000 inches   |
| Overall Height:  |
| 18.000 inches  |
| Overall Width:   |
| 11.094 inches  |
| Current Type:  |
| Ac   |
| Environmental Protection:  |
| Weatherproof   |
| Contact Quantity:  |
| 2  |
| Tube Length:   |
| 51.000 inches  |
| Contact Type:  |
| Female prong   |
| Dial Scale Marking Color:  |
| White and white and white  |
| Scale Quantity:  |
| 1 and 1 and 1  |
| Scale Name:  |
| Sight and line and line of sight   |
| Knob Location:   |
| Gyro housing top and gyro housing bottom and under azimuth scale                                 |
| Handle Quantity:   |
| 1 and 1 and 1  |
| Electrical Connection Quantity:  |
| 1  |
| Electrical Connection Controlling Agency:  |
| Af   |
| Electrical Connection Identifying Number:  |
| Part no. 38a1505   |
| Scale Background Color:  |
| Black and black  |
| Knob Quantity:   |
| 1 and 1 and 1  |
| Mounting Method:   |
| Fixed flange   |
| Scale Range:   |
| 16 degrees fwd to 87 degrees rearward; 0 to 360 deg; 20 degrees left and 20 degrees right from 0 |
| Scale Smallest Increment Graduation:   |

1 deg; 1 deg; 1 deg

## **NSN 6605-00-224-3394**Drift Meter - Page 2 of 2



| Knob Name:   |
|--|
| Light control and caging and tangent screw                               |
| Reticle Stabilization Characteristic:                                    |
| Gyro stabilized  |
| Reticle Illumination:  |
| Provided   |
| Handle Name:   |
| Light filter and light filter and sight control line                     |
| Handle Location:   |
| Filter housing back and filter housing back and filter housing left side |
| Voltage In Volts:  |
| 110.0  |
| Phase:   |
| Single   |
| Frequency In Hertz:  |
| 400.0  |
| Specification Or Standard:   |
| B-3 type   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| T261-a   |