Induction Compass Transmitter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6605-01-071-1249

| Overall Length: |
|---|
| 4.901 inches |
| Overall Height: |
| 2.067 inches |
| Overall Width: |
| 3.500 inches |
| Shock Mount: |
| Not provided |
| Electrical Connection Quantity: |
| 1 |
| Electrical Connection Controlling Agency: |
| Milstd |
| Electrical Connection Identifying Number: |
| Ms24266r12t12p |
| Connector Mating Method: |
| External |
| Mounting Method: |
| Flange |
| Heeling Correctors: |
| Not provided |
| Stabilizing Feature: |
| Not included |
| Direction Sensing Element Type: |
| Fluxgate |
| Transmitting Coil Voltage In Volts: |
| 23.5 |
| Transmitting Coil Frequency In Hertz: |
| 400.0 |
| Electrical Connection Cable Watertight Gland: |
| Not furnished |
| Connector Prong Quantity: |
| 12 |
| Quadrantal Spheres: |
| Not included |
| Special Features: |
| Preindexed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

NSN 6605-01-071-1249

Induction Compass Transmitter - Page 2 of 2

Fiig: T261-h

