

View Online at <https://aerobasegroup.com/nsn/6610-00-160-0905>

Scale Marking And Surface Finish:

Letters nonluminous and lined increments nonluminous and numerals nonluminous

Width:

Between 2.360 inches and 2.440 inches

Scale Division Quantity:

17 1st indicator 1st scale

Current Type:

Ac/dc

Ac Voltage Rating:

Between 380.0 volts and 420.0 volts

Dc Voltage Rating:

5.0 volts

Frequency Rating:

400.0 hertz

Depth:

7.500 inches

End Application:

High preformance aircraft

Presentation Type:

Drum dial and drop flags

Scale Range:

-80.0 to 80.0 degrees 1st indicator single scale

Electrical Connection Quantity:

1

Electrical Connection Identifying Number:

Ms3112e10-6p

Pointer Finish:

Nonluminous 1st pointer

Pointer Purpose:

Pitch & roll of aircraft

Pointer Type:

Indicating 1st pointer

Illumination Color Generation Method:

Incandescence and integral light

Mounting Facility Type And Quantity:

1 bezel and 3 screw

Accuracy Rating:

0.25 degree angular calibration range 1st indicator single scale

Dial Outside Diameter:

Between 2.234 inches and 2.254 inches

Phase:

Three

Special Features:

H1 knob for caging internal gyroscope and positioning miniature airplane indicator, flag indicating on/off; white lighting, lightin circuit 5vac, 5vdc; maximum wieght 2.5lbs; air force tech order 5f8-10-9-4

Height:

Between 2.360 inches and 2.440 inches

Supplementary Features:

Displays attitude information. Indicator contains its own vertical gyroscope, displays pitch & roll information. Operates independant of other aircraft systems except for operating power

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A532a0