NSN 6610-01-448-2335

Flight Information Display Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6610-01-448-2335

9.000 inches Overall Height: 8.500 inches Overall Width: 11.250 inches End Application: Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cibbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 (and by the connectors per mil-c-38999; 480 (
Overall Height: 8.500 inches Overall Width: 11.250 inches End Application: Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 ince by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure:	Overall Length:
8.500 inches Overall Width: 11.250 inches End Application: Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure:	9.000 inches
Overall Width: 11.250 inches End Application: Mf33) Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Overall Height:
End Application: Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fitig:	8.500 inches
End Application: Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Overall Width:
Mf53j Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	11.250 inches
Features Provided: Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure:	End Application:
Electrostatic sensitive Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Mf53j
Criticality Code Justification: Cbbl Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Features Provided:
Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Electrostatic sensitive
Special Features: Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Criticality Code Justification:
Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480 line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: — Demilitarization: Yes - demil/mli Fiig:	Cbbl
line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232 interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Special Features:
interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Power 28 vdc, 215 watts, 330 watts max; mounting to cockpit panel with 4 bolts; 3 interface cables with connectors per mil-c-38999; 480
stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker controls Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	line by 640 pixel active matrix liquid crystal display; night vision compatible; sunlight readable per mil-i-85762; control and status via rs232
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	interface; video interface: displays 525 line red/green/blue 4: 3 aspect ratio video and 875 line monochrone 4: 3 aspect ratio video per
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	stanag 3350; front bezel contains 12 side function keys, an off/normal/test switch, a day/night switch, and brightness and contrast rocker
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	controls
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A23900	Fiig:
	A23900