

View Online at <https://aerobasegroup.com/nsn/6615-00-237-6160>

**Mounting Provision:**

Unthreaded mounting holes

**Overall Height:**

4.030 inches

**Overall Width:**

4.410 inches

**Bore Diameter:**

0.839 inches

**Compressed Length:**

9.040 inches

**Extended Length:**

9.540 inches

**Mounting Provision Arrangement Style:**

Three hole

**Integral Valve Operation Method:**

Hydraulic

**Design Characteristics:**

Double acting single cylinder

**Mounting Facility Diameter:**

0.274 inches

**Center To Center Distance Between Mounting Provisions:**

3.350 inches

**Special Features:**

Manufacturers name: servoactuator; electrical input solenoid 28 vdc, synchro transformer input 25 vac, 400 hz, servo rated current +/- 15 ma at 30 v; centering force 25 lbs ; load limiter valves set to limit output force to 420-500 lbs; operating medium mil-h-5606 hydraulic fluid; operating pressure 3000 psi pressure port and 1000 psi return port; proof pressure 4500 psi pressure port and 1500 psi return port; burst pressure 7500 psi pressure port and 2500 psi return port; actuator bore diameter 0.837 to 0.839 inch, actuator rod diameter 0.621 to 0.622 inch; actuator effective area 0.248 sq inch

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A34200