NSN 6620-00-557-0363

Pressure Indicator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6620-00-557-0363

Scale Marking And Surface Finish: Numerals fluorescent and lined increments fluorescent Current Type: Ac Dc Voltage Rating: 26.0 volts Frequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Current Type: Ac Dc Voltage Rating: 26.0 volts Frequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Dc Voltage Rating: 26.0 volts Frequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Dc Voltage Rating: 26.0 volts Frequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Prequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Frequency Rating: 400.0 hertz Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Contact Quantity: 4 Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Contact Type: Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Pin Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Scale Range: +0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
+0.1/+200.0 pounds per square inch single indicator single scale Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Electrical Connection Quantity: 1 Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Electrical Connection Identifying Number: An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
An3102-14s-2p Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Illumination Color Generation Method: Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Fluorescence Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Accuracy Rating: 10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
10.0 pounds per square inch single indicator single scale Features Provided: Encapsulated Phase: Single Special Features:
Features Provided: Encapsulated Phase: Single Special Features:
Encapsulated Phase: Single Special Features:
Phase: Single Special Features:
Single Special Features:
Special Features:
dimensions per mil-i-7087 and ms 28010-3
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A533y0