NSN 6620-00-557-5558

Pressure Indicator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6620-00-557-5558 | | | | | | |
|---|--|--|--|--|--|--|
| Scale Marking And Surface Finish: | | | | | | |
| Letters fluorescent and lined increments fluorescent and numerals fluorescent | | | | | | |
| Width: | | | | | | |
| 3.250 inches | | | | | | |
| Length: | | | | | | |
| 5.156 inches | | | | | | |
| Current Type: | | | | | | |
| Ac | | | | | | |
| Dc Voltage Rating: | | | | | | |
| 26.0 volts | | | | | | |
| Frequency Rating: | | | | | | |
| 400.0 hertz | | | | | | |
| Contact Quantity: | | | | | | |
| 7 | | | | | | |
| Contact Type: | | | | | | |
| Pin | | | | | | |
| Scale Range: | | | | | | |
| +0.1/+200.0 pounds per square inch single indicator single scale | | | | | | |
| Individual Marking: | | | | | | |
| 1; 2 | | | | | | |
| Electrical Connection Quantity: | | | | | | |
| 1 | | | | | | |
| Electrical Connection Identifying Number: | | | | | | |
| And10066a-16s-1p or 10066d-16s-1p | | | | | | |
| Illumination Color Generation Method: | | | | | | |
| Fluorescence | | | | | | |
| Mounting Stud Diameter: | | | | | | |
| 0.170 inches | | | | | | |
| Accuracy Rating: | | | | | | |
| 10.0 pounds per square inch single indicator single scale | | | | | | |
| Features Provided: | | | | | | |
| Encapsulated | | | | | | |
| Phase: | | | | | | |
| Single | | | | | | |
| Height: | | | | | | |
| 3.250 inches | | | | | | |
| Specification Or Standard: | | | | | | |
| B/9c/12 type | | | | | | |

Shelf Life: N/a

Fsc Application Data:
Engine instrument aircraft

NSN 6620-00-557-5558

Pressure Indicator - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A533y0