

View Online at <https://aerobasegroup.com/nsn/6620-00-800-5579>

**Diameter:**

2.000 inches

**Length:**

6.125 inches

**Current Type:**

Ac

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

400.0 hertz

**Contact Quantity:**

12

**Contact Type:**

Pin

**Usage Design:**

Rate of flow

**Presentation Type:**

Dial

**Scale Range:**

+0.0/+5000.0 pounds per hour single indicator single scale

**Individual Marking:**

Fuel flow; pph x 1000

**Electrical Connection Quantity:**

1

**Electrical Connection Identifying Number:**

8202-13-12pm-pp or mc14h-13-12pn or equivalent

**Pointer Purpose:**

Indicate current rate of flow

**Pointer Type:**

Indicating single pointer

**Mounting Facility Type And Quantity:**

1 clamp

**Accuracy Rating:**

100.0 pounds per hour single indicator single scale

**Product Name:**

Indicator, rate of flow, 0-5, 000 pph, integrally lighted

**Dial Outside Diameter:**

1.750 inches

**Phase:**

Single

**Special Features:**

Pcase conforms to ms33639 and is hermetically sealed; case finish lusterless black per color no. 37038 of fed-std-595; includes filler tube; power consumption 8.0 va; weight 1.5 lbs; integral lighting per mil-I-27160

**Supplementary Features:**

Indicator designed to indicate the rate of flow in pounds per hour when connected with a tru-6/a fuel flow transmitter conforming to mil-t-26298

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A534d0